

PROFESSIONAL LINE

Walk-behind floor scrubber driers

A1 36



Standard equipment



• 5.511.1346 PPL brush Ø 360 mm - 15"



4.508.1100
Front squeegee blade
L.537 mm - Th. 2.5 mm
4.508.1101
Rear squeegee blade
L.590 mm - Th. 3 mm



• 0.108.0061 On-board Battery charger 12V 8A

only for model code: 8.518.0065 - 8.518.0007



• 0.107.0061 Maintenance free battery 12V 55Ah BT DC 4.2

only for model code: 8.518.0007



Watch the video on youtube: www.youtube.com/fasavideo

| | A1 36 E | A1 36 B | A1 36 B |
|--------------------------|-------------|---------------|-------------------------|
| Code | 8.518.0008 | 8.518.0065 | 8.518.0007 |
| Power supply | 230 V~50 Hz | 1 x 12 V | 1 x 12 V |
| Equipped with | - | Batt. charger | Batteries/batt. charger |
| Scrubbing width | 360 mm | 360 mm | 360 mm |
| Squeegee width | 460 mm | 460 mm | 460 mm |
| Max working capacity | 1260 m²/h | 1260 m2/h | 1260 m²/h |
| Detergent tank capacity | 11 l. | 11 l. | 11 l. |
| Recovery tank capacity | 12/13 l. | 12/13 l. | 12/13 l. |
| Traction type | mechanical | mechanical | mechanical |
| Brush/Vacuum motor power | 370/400 W | 250/180 W | 250/180 W |
| | | | |

A1 36

• Suitable to work in high congested areas like small shops, offices, kitchens, schools, hospitals, bars, gyms, restaurants • Adjustable flow (automatic start-stop with solenoid valve) of the detergent solution depending on type of surface • Brush with quick release • Removable recovery tank • Available in battery version (36B) with integrated battery charger with data memory and for any type of batteries • Battery included • Squeegee lifting lever • Compact reclining handle with control switches • Easy access and simple service of the components.

PROFESSIONAL LINE



Walk-behind floor scrubber driers



The unit can be supplied mains (15 m cable available) or battery powered. Reclining handle: fit on any operator's height and allowing the perfect cleaning also on 90° corners. Shock-absorbing covers, simple cleaning of the recovery tank, non

marking wheels.
Easy access to
mechanical parts (easy
maintenance of each
component), removable
recovery tank without
tools.





User friendly analogic control panel. Control lever for brush operation and detergent water outflow.

General ON/OFF switch, brush and vacuum motor switch, solenoid valve operation switch.

Parabolic squeegee, easy rubber blades replacement. The floating brush plate and squeegee grant the right cleaning pressure on any type of floor.



Optional accessories:



• 0.107.0050 Battery AGM 12V 55Ah C5



• 0.108.0051 Booster battery charger



• 4.508.1058 Polyurethane front blade L.537 TH. 2,5

• 4.508.1059 Polyurethane rear blade L.590 TH. 3



• 5.511.1413 Tynex brush Ø 360 mm-14"

• 5.511.1411 PPL 0,03 brush Ø 360 mm-14"

• 5.511.1412 PES brush Ø 360 mm-14"



• 5.511.1129 EWU pad driver Ø 360mm-14"



• 6.508.0143 Abrasive pad Ø 381 mm-15"

- beige (5 pcs.)

• 6.508.0144

Abrasive pad Ø 381 mm-15"

- green (5 pcs.)

• 6.508.0141

Abrasive pad Ø 381 mm-15"

- black (5 pcs.)



• 4.512.0068 Extension electric cord 15 m with Schuko plug