

# Walk-behind floor scrubber driers

### Standard equipment



• 5.511.1688 PPL brush Ø 430 mm - 17"



4.508.X468
Front squeegee blade L.830 mm Shore 40 Th. 2.5 mm
4.508.X467
Rear squeegee blade L.870 mm Shore 40 Th. 3 mm



• 0.108.0042 On-board Battery charger CBHD1 24V 10A only for model code: 8.524.1003 8.524.0003



• 2 x 0.107.0061 Maintenance free battery 12 MFP 50 - 12V 50Ah only for model code: 8.524.0003

#### Other available versions:

• 8.524.1003 - A3 45 without batteries



## Watch the video on youtube: www.youtube.com/fasavideo

	A3 45E	A3 45*
Code	8.524.3303	8.524.0003
Power supply	230V~50Hz	24V DC
Scrubbing width	450 mm	450 mm
Squeegee width	800 mm	800 mm
Max working capacity	1 <i>575</i> m2/h	1 <i>575</i> m2/h
Detergent tank capacity	25 l-6.61 gal	25 l-6.61 gal
Recovery tank capacity	25-28	25-28
Traction type	mechanical	mechanical
Brush motor power	550 W	450 W
Vacuum motor power	400 W	370 W

### A3 45

• Suitable to work in high congested areas like wellness centres and medical environments in general, gyms, retail outlets, car shops, sales points and health care • Solution water filter and solenoid valve (battery model only) • User friendly control panel • Hour meter (optional) • Chemical dosing system on request • Recovery water tank with visual inspection • Reclining handle with control lever (battery model only) • Low noise operation thanks to the protected positioning of vacuum motor • Recovery tank drain hose with adjustable flow system • Indicator of the solution water tank fill level • Easy access to the recovery tank • Non-marking wheels.

# Walk-behind floor scrubber driers



User friendly analogic control panel. Control lever for brush operation and detergent water outflow. ON/OFF and battery cutout key switch, brush and vacuum motor switch, detergent dosing knob (optional), Thermal circuit breaker to protect

vacuum and brush motor,
battery level indicator,
hour meter (optional).
Automatic detergent
dosing system on request.
Indicator of clean water
tank level. Detergent
solution regulation.
Recovery tank drain
hose with adjustable



flow system. Easy access to recovery water tank with visual inspection. Extremely silent (62 dB) thanks to the particular housing of the vacuum motor and the use of soundproofing material.

Thanks to the special squeegee support it is easily possible the tilting of the machine to carry out the drying of the floor without scrubbing. The oversize wheels facilitate maneuverability and effortless use.





### Optional accessories:



• 0.107.0065 Battery AGM 12V 60Ah C5



4.508.1178 Polyurethane front blade L.830 TH. 3
4.508.1177 Polyurethane rear blade L.870 TH. 4



• 5.511.1713 Tynex brush Ø 430 mm-17" • 5.511.1711 PPL 0,03 brush Ø 430 mm-17" • 5.511.1712 PES brush Ø 430 mm - 17"



• 5.511.1095 EWU pad driver Ø 430 mm-17"



• 6.508.0032 Abrasive pad Ø 430 mm-17" - beige (5 pcs.) • 6.508.0039 Abrasive pad Ø 430 mm-17" - green (5 pcs.) • 6.508.0046 Abrasive pad Ø 430 mm-17" - black (5 pcs.)



• 4.512.0068 Extension electric cord 15 m with Schuko plug

• 5.511.1687 Automatic detergent dosing system on request.